



## Features:

- **USB spec. 2.0 full-speed compatible**
- **Noise cancelling microphone**  
With highest voice recognition industry rating
- **Pro-Flex wire microphone boom**  
Allows for perfect placement of microphone
- **40mm speaker with CD quality sound**
- **Comfortable foam ear cushion**  
Reversible for left or right side usage
- **Microphone windsock**  
For minimal breath popping
- **In-line Digital Volume/Mute Controls**
- **Stainless steel adjustable head band**  
Folds flat for storage
- **Extra long 8 foot shield cable**



Parameter	Value
<b>Operation</b>	
Power	USB
Microphone Input	1 Channel
Audio Output	2 Channel stereo
<b>Microphone</b>	
Noise Cancellation	5. dB/octave
Frequency Range	100-10,000 Hz
Electrical Signal-to-Noise Ratio	>60 dB
Sensitivity at 1 kHz (0 dB = 1 V/Pa)	-44 dB
Current Consumption	<0.5 mA
A/D Conversion Resolution	16 bit
THD + N	-76 dB
<b>Speaker</b>	
Frequency Range	50-20,000 Hz
Coil Resistance	32 ohm
Sound Output from 1 kHz 1mW Input (0 dB = 20 µPa)	114 dB
Maximum Input Power	40 mW
D/A Conversion Resolution	16 bit
THD + N	-71 dB



USB 2.0 Compatible



Proprietary Mic Design



Digital Volume/Mute Control